MAseries MLA112


Line Array System




The MLA112 is a small and medium scale line array loudspeaker for long throw distance scale sound reinforcement, fitted with one 12" neodymium LF driver and two 1" neodymium HF driver coupled to a patent line array horn,made of high quality plywood with polyurea waterproof paint. All rigging parts are made of aluminium alloy.

MLA112是一款中型、高精度线性阵列扬声器系统,它具有较小的体积和较轻重量,却有较大的声压级,应用低失真中低音单元及 线性号角,能忠实还原规定范围内音频信号。吊挂系统采用铝合金材质,安装快捷及保证安全。一只12"高效率强磁中低音单元,一只声透镜号角配置二只1"喉口44芯强磁高音驱动器;箱体采用多层复合夹板,聚脲喷涂。

CONFIGURATION







MODEL FREQUENCY RESPONSE(-3dB) FREQUENCY RESPONSE(-10dB) DRIVERS

RATED POWER SENSITIVITY MAXIMUM SPL IMPEDANCE DISPERSION(-6dB)

CROSSOVER FREQUENCIES
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

FEATURES

- High quality plywood with polyurea waterproof paint
- High quality neodymium components
- Patent line array horn
- Small cabinet with light weight, but with high SPL
- Passive or Bi-amp operation
- Convenient for hanging tripod and stacking
- Good used for moving performance, small scale theater, stadium and odeums.

产品特征

- ●高质量单元配置,专利线性号角:高保真音质, 投射精确
- ●内、外置分频选择,操作简便灵活又可最大发 挥使用者的技术优势
- ●方便简捷的吊挂方式:可吊挂,可堆码,可支撑, 安装快捷、灵活
- ●超长品质保证期:品质与信心的保证

适用范围

- ●中小型流动演出
- ●多功能厅、酒店会所

MLA112

50Hz-18kHz

45Hz-20kHz

1×12"(300mm)/3"voice coil LF

2×1"(25mm)/1.7"voice coil HF

400W RMS,1600W peak

98dB 1watt/1meter

124dB continuous,130dB peak

8 ohms nominal

Horizontal covrage: 100°

Vertical coverage: Varies, depending on

array length and configuration

2kHz passive

2×Speakon NL4

 $522mm \times 487mm \times 635mm$

21 kg/pc

25 kg/pc

www.fdbaudio.com Page 22